

# RAC

# 1000/1100



NVIDIA® Jetson AGX Orin™ Rugged AI Computing System



^ Automated Agricultural Machinery



- Advanced NVIDIA® Jetson AGX Orin™ platform delivers up to 275 TOPS AI performance
- The latest NVIDIA Ampere™ architecture, featuring with 2048 NVIDIA® CUDA® cores and 64 Tensor cores
- Supports 8 GMSL 1/2 automotive cameras with Fakra-Z connectors
- IP67 Anti-dust and Waterproof Chassis design
- 1 PCIe Gen3 x8 expansion slot supports optional multiple 10GigE/PoE LAN/USB connections (by request)
- 2 Isolated CAN-FD, 2 COM RS-232/422/485
- 6 GigE LAN with 4 PoE+, 2 USB 3.1, 1 Digital Display supports 4K60
- DC 9V to 50V wide range power input, Software Ignition Power Control

v Construction Automation



^ Mobile Robotics



# Vecow

# Specifications

## System

CPU	<b>R32</b> : 8-core Arm® Cortex®-A78AE v8.2 64-bit CPU <b>R64</b> : 12-core Arm® Cortex®-A78AE v8.2 64-bit CPU <b>IND</b> : 12-core Arm® Cortex®-A78AE v8.2 64-bit CPU
GPU	<b>R32</b> : 1792-core NVIDIA Ampere™ architecture GPU with 56 Tensor Cores <b>R64</b> : 2048-core NVIDIA Ampere™ architecture GPU with 64 Tensor Cores <b>IND</b> : 2048-core NVIDIA Ampere™ architecture GPU with 64 Tensor Cores
DL Accelerator	2x NVDLA Engines
Memory	<b>R32</b> : 1 32GB LPDDR5 DRAM <b>R64</b> : 1 64GB LPDDR5 DRAM <b>IND</b> : 1 64GB LPDDR5 DRAM
OS	- Linux - NVIDIA JetPack SDK

## I/O Interface

USB	2 USB 3.1 (M12)
Serial	2 COM RS-232/422/485 (M12 A-coded)
LAN	2 GigE LAN (M12 X-coded)
HDMI	1 HDMI 2.1 (M12)
CAN Bus	2 Isolated CAN Bus support CAN FD (M12 A-coded)
Flash	1 Micro USB OS flash port
Button	1 Power Button with LED, 1 Recovery button

## Expansion

PCIe	1 PCIe x8 Slot (by request)
M.2	- 1 M.2 Key B Socket (3042/3052) - 1 M.2 Key E Socket (2230)

## Graphics

Interface	1 Digital Display, up to 4K60
Video Encode	<b>R32</b> : 1x 4K @60, 3x 4K @30, 6x 1080p @60 (HEVC) <b>R64</b> : 2x 4K @60, 4x 4K @30, 8x 1080p @60 (HEVC)
Video Decode	<b>R32</b> : 1x 8K @30, 4x 4K @30, 9x 1080p @60 (HEVC) <b>R64</b> : 1x 8K @30, 7x 4K @30, 11x 1080p @60 (HEVC)

## Camera (RAC-1000)

GMSL	8 Fakra-Z connectors for GMSL 1/2 automotive cameras
------	--

## Storage

M.2	2 M.2 Key M socket (2280)
eMMC	1 eMMC 5.1, 64GB

## Ethernet

LAN 1	10/100/1000 Base-T Ethernet GigE LAN, X-coded M12 Connector
LAN 2	10/100/1000 Base-T Ethernet GigE LAN, X-coded M12 Connector

## PoE (RAC-1100)

LAN 3 to LAN 6	IEEE 802.3at (25.5W/48V) GigE PoE+ LAN, X-coded M12 Connector
Total PoE power budget support up to 60W at 25°C, 30W at 70°C	

## Power

Power Input	DC 9V to 50V
Power Interface	4-pin K-Code M12 connector
Ignition Control	16-mode Software Ignition Control

## Mechanical

Dimensions	260 mm x 330 mm x 80 mm (10.23" x 13" x 3.14")
Weight	7 kg (15.43 lb)
Mounting	Wallmount

## Environment

Operating Temperature	<b>30W TDP Mode</b> : -25°C to 70°C (-13°F to 158°F), with 0.63 m/s air flow <b>50W TDP Mode</b> : -25°C to 55°C (-13°F to 131°F), with 0.63 m/s air flow
Storage Temperature	-40°C to 85°C (-40°F to 185°F)
Humidity	5% to 95% Humidity, non-condensing
Relative Humidity	95% @70°C
Shock	Operating, MIL-STD-810G, Method 516.7, Procedure I
Vibration	Operating, MIL-STD-810G, Method 514.6, Procedure I, Category 4
EMC	CE, FCC, EN50155, EN50121-3-2, IP67

\* All product information may subject to change without prior notice.  
\* The rights of all brand names, product names and trademarks belong to their respective owners.  
Copyright © 2024 Vecow Co., Ltd. All rights reserved.

# Order Information

Model Name	Platform	RAM	LAN	USB 3.1	Serial	Iso. CAN	GMSL	PoE*	M.2
RAC-1000-R32	Jetson AGX Orin	32GB	2	2	2	2	8	-	4
RAC-1000-R64		64GB							
RAC-1000-IND	Jetson AGX Orin Industrial	64GB							
RAC-1100-R32	Jetson AGX Orin	32GB	6	2	2	2	-	4	4
RAC-1100-R64		64GB							
RAC-1100-IND	Jetson AGX Orin Industrial	64GB							

## Accessories

PWA-160WB-WT	160W, 24V, 85V AC to 264V AC Power Adapter with 3-pin Terminal Block, Wide Temperature -30°C to +70°C
PWA-180WB	180W, 24V, 90V AC to 264V AC Power Adapter with 3-pin Terminal Block
PWA-280WB-WT	280W, 24V, 85V AC to 264V AC Power Adapter with 3-pin Terminal Block, Wide Temperature -30°C to +70°C
GMSL Camera Kit	GMSL Camera with Fakra-Z connector
M.2 Storage Module	M.2 Key M/Key B PCIe Storage Module

# Dimensions & Drawing

Unit : mm (inch)

